



## MODEL 36A Compu-Cut Round Material Cutter

The new model 36A has been specifically designed to provide clean square and accurate cuts on a broad range of wire, cable and tubing. This machine's unique design supports the material being cut on both sides of the cutting blade ensuring clean square cuts. The Model 36A uses a powerful feed belt material transport along with a pneumatically operated blade mechanism that utilizes a standard utility knife cutting blade. This unit excels when processing flexible and rigid type tubing including split loom, viton, pvc, rubber and many more. Our user friendly menu driven software makes the model 36A simple to program and easy to operate. Some key features of this new machine are extremely low operating costs, the machine utilizes only 1 cut blade which is a standard utility knife blade, costing only pennies! Our feed belt material transport is not only accurate and powerful but extremely durable. plus it will not damage or crush the material being processed. With software features that include a large memory storage, English or Metric operation, Batch Processing and Kitting the new Model 36A will increase speed, accuracy and efficiency. Every Carpenter machine comes with a durable powder coat finish and a standard 1 year limited warranty.

### STANDARD FEATURES:

- Powerful Feed Belt Material Transport
- Pneumatic Blade Mechanism
- Material Loading and Unloading
- Utility Knife Cut Blade
- 100 Kit Program Memory Storage
- 500 Single Program Memory
- Safety Guard with Interlock Switch
- Programmable Machine Password
- 5 programmable Feed Speeds
- Inches or Millimeters Selectable
- "Material Cut" Sensor
- "Out of Material" Sensor
- Auto Switching Power Supply
- User Friendly Menu Driven Software
- 1-Input & 1-Exit Guide with Machine
- 1 Year Limited Warranty

### SPECIFICATIONS:

<b>Cut Length</b>	.05" to 9,999.99" or 1.2mm to 99999.9mm
<b>Length Increments</b>	.01"
<b>Amount</b>	1 to 999,999
<b>Round Material</b>	1.0" or 25.4mm (Max) Material Dependent
<b>Air Supply</b>	80-100 PSI or 5.4-6.2 BAR Clean, Filtered & Lubricated
<b>Voltage</b>	88 to 264 VAC, 47 to 63Hz, 4 Amp (Auto Switching)
<b>Production Rate</b>	5000 4.00" pcs/hr
<b>Warranty</b>	1 Year Limited Warranty
<b>Dimensions</b>	13.7" W x 11.0" H x 17.0" D (including safety guard)
<b>Weight</b>	52 lbs / 24kg